



Z994R

Key Specs

Engine Manufacturer/Model - 3TNV80F

Fuel Tank Capacity - 43.5 L

Transmission - Dual hydrostatic wheel drive TuffTorq heavy-duty ground drive with cross porting for improved cooling

Forward Speed - Minimum - 0.0 km/h

Forward Speed - Maximum - 17.0 km/h

Reverse Speed - Minimum - 0.0 km/h

Reverse Speed - Maximum - 7.2 km/h

Caster Wheels - 13x6.5-6

Mower Deck Size - 137-cm (54-in.) 7Iron™ PRO side-discharge
152-cm (60-in.) 7Iron™ PRO side-discharge
152-cm (60-in.) FastBack™ PRO rear-discharge

Engine

Engine Manufacturer/Model - 3TNV80F

Engine Power - Gross - 3200.0 rpm

Engine Power - Gross - 17.3 kW

Rated Engine RPM - 3200.0 rpm

Cylinders - 3

Displacement - 1267.0 cc

Injection - Indirect

Fuel Type - Diesel or Biodiesel (up to B20)

Fuel Tank Capacity - 43.5 L

Air Cleaner - Heavy-duty canister, dry type with safety element and air-restriction indicator

Engine

Battery - 12 V

Drivetrain

Transmission - Dual hydrostatic wheel drive TuffTorq heavy-duty ground drive with cross porting for improved cooling

Speed And Direction Control - Twin lever, zero turn

Travel Speed

Forward Speed - Minimum - 0.0 km/h

Forward Speed - Maximum - 17.0 km/h

Reverse Speed - Minimum - 0.0 km/h

Reverse Speed - Maximum - 7.2 km/h

Dimensions

Length - 2.25 m

Overall Width - 1.62 m

Overall Height With ROPS - 185.0 cm

Overall Height With ROPS Folded - 119.0 cm

Shipping Weight - 821 kg

Mower Decks

Deck Thickness - 7.0 gauge

Deck Thickness - 0.45 cm

Caster Wheels - 13x6.5-6

Mower Deck Type - Flat free

Mower Deck Size - 137-cm (54-in.) 7Iron™ PRO side-discharge

152-cm (60-in.) 7Iron™ PRO side-discharge

152-cm (60-in.) FastBack™ PRO rear-discharge

Additional Information

Date Collected - 2025-12-01T00:00:00